

LOFPLEAT™ HF-G high flow capacity fiberglass filter cartridges

Eaton's LOFPLEAT HF-G filter cartridges can be used in a variety of applications where high flow capacity is required including fuel oils, chemicals, petrochemicals, solvents and oil and gas.

LOFPLEAT HF-G filter cartridges are designed with pleated micro fiberglass filter material construction to provide a high total surface area. A single LPHF-G filter cartridge can replace several standard cartridge elements. Change-outs are quick and easy. Unlike standard design filter cartridges, the flow is inside out. The result is higher dirt-holding capacity.

Features and benefits

- Higher flow capacity reduces required number of filter cartridges
- Lower initial costs with smaller filter housings
- Less labor required for change-outs
- Available with absolute rated filter material at 1 to 20 µm retention ratings

- Inside-out flow for greater dirt-holding capacity
- Capable of flow rates up to 1,892.5 l/min in a single 60" length
- Can be retrofitted in most competitive high-flow housings
- Thermally bonded construction

Design

Filter material

Micro fiberglass

Cage

Polyester or polypropylene

End caps

Polyacetal or polypropylene

Gaskets/O-rings

EPDM (standard), silicone, Buna-N, FPM

Retention ratings

1, 2.5, 4.5, 10, 20 µm
@ 99.9% efficiency

Technical data

Nominal lengths

20", 40", 60" (50.8, 101.6, 152.4 cm)

Outside diameter

6" (152.4 cm)

Surface area

2.4 m² per 20" element

Max. operating temperatures

Polyacetal: 110 °C
Polypropylene: 82 °C

Max. differential pressures

5.2 bar @ 21 °C
1.4 bar @ 82 °C
3.4 bar @ 110 °C

Recommended differential change-out pressure for disposal

2.4 bar

Max. flow rates

20" element: 662 l/min
40" element: 1,325 l/min
60" element: 1,892 l/min



Powering Business Worldwide


LOFPLEAT HF-G high flow capacity fiberglass filter cartridges

Element pressure drop

	mbar/m³/h		
	20"	40"	60"
1	11.9419	5.9709	3.9806
2.5	5.5385	2.7692	1.8462
4.5	4.3549	2.1775	1.4516
10	2.8830	1.4415	0.9610
20	2.0940	1.0470	0.6980

Note: For chemical compatibility, flow rates, and temperature requirements please consult the factory or your local Eaton distributor.

Ordering code



Efficiency of retention

Beta ratio efficiency of retention	Beta 1000 99.90%	Beta 100 99%	Beta 10 90%
1 µm	1	0.6	0.2
2.5 µm	3	2	1.5
4.5 µm	5	4	3
10 µm	10	8.5	6.5
20 µm	22	19	14

$$\text{Beta ratio} = \frac{\text{Upstream particle counts}}{\text{Downstream particle counts}}$$

The micron ratings shown at various efficiency and beta ratio value levels were determined through laboratory testing, and can be used as a guide for selecting cartridges and estimating their performance. Under actual field conditions, results may vary somewhat from the values shown due to the variability of filtration parameters. Testing was conducted using the single-pass test method, water at 9.46 l/min/10" cartridge. Contaminants included latex beads, coarse and fine test dust. Removal efficiencies were determined using dual laser source particle counters.

Contact your **authorized Eaton distributor** today:

Commercial Industrial Supply

1444 East Main Street
Rock Hill, SC 29730 USA

Tel: (866) 777-8001

Email: info@emailcis.com