





Contaminants Reduced:

- Sediment, Dirt and Rust
- Chlorine Taste and Odor





Tested and certified to NSF Standard 42 for material safety only

Residential/Commercial Filtration Applications

Standard Features

- Manufactured in China
- Environmentally-friendly coconut shell granular activated carbon (GAC) filter
- Ideal for point-of-entry (POE) and other high flow rate application
- Compatible with Culligan® RFC-BBSA, Pentek® RFC-BB, Omnifilter® TO8, GE FXHTC, Aqua-Pure® AP817, American Plumber® WRC25HD, and Whirlpool® WHEF-WHPCBB
- Drop-in cartridge style

Product Specifications

Filter Media

Coconut shell granular activated carbon (GAC)

Micron Rating (Nominal)

25 microns

Dimensions

4-1/2" dia. x 10"

Capacity

10,000 gallons

Operating Temperature

40 to 100°F (4.4 to 37.8°C)

Operating Pressure

30 to 100 psi

Maximum Flow Rate

3 gpm

Change Frequency

6 months

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



Contact your **authorized NeoLogic distributor** today: **Commercial Industrial Supply**

1444 E. Main St., Rock Hill, SC 29730 **Tel:** (866) 777-8001 **Email:** info@emailcis.com